




TECHNICAL SPECIFICATIONS	
CONTACT CARRIER MATERIAL	NYLON OR TPU
MOLDED HEAD MATERIAL/COLOR	TPU/YELLOW
CONTACT MATERIAL/PLATING	BRASS/GOLD
COUPLING NUT MATERIAL/PLATING	ZINC DIE-CAST/NICKEL
RATED CURRENT	16A
RATED VOLTAGE	63VDC
OUTER CABLE JACKET MATERIAL/COLOR	PVC/BLACK
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS(AWG)	5×14AWG
OPERATING TEMPERATURE	-25°C~ + 85°C
PROTECTION CLASS	IEC IP67, IN MATED CONDITION
XXXXXX	XXXXXX

REV	CHG.	DATE	DESCRIPTION	REVISION

MALE END VIEW



1. BN
2. WH
3. BU
4. BK
5. GY



SOURCE DRAWING-FOR REFERENCE ONLY


APPROVED BY		DATE	
CHECKED BY	ALEX	DATE	
DRAWING BY		DATE	2023.8.9



CABLE LENGTH	TOLERANCE	
	ALL LENGTHS	+4%(OR 50mm) OF LENGTH -0%(OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE	
0-7mm	±1.0mm	
8-29mm	±1.5mm	
30-49mm	±2.0mm	
50-99mm	±3.0mm	
70-100mm	±4.0mm	
over 100mm	±5.0mm	

UNITS mm

1st Angle Projection



DESCRIPTION:
CBL-M12LM5-OP-2

PART NO.

REV	A	SHEET	1 OF 1
-----	---	-------	--------