

TECHNIACAL SPECIFICATIONS	
CONTACT CARRIER MATERIAL	NYLON OR TPU
MOLDED HEAD MATERIAL/COLOR	TPU/YELLOW
CONTACT MATERIAL/PLATING	BRASS/GOLD
COUPLING NUT MATERIAL/PLATING	ZINC DIE-CAST/NICKEL
RATED CURRENT	1.5A
RATED VOLTAGE	480V
OUTER CABLE JACKET MATERIAL/COLOR	PUR/GREEN
CONDUCTOR INSULATION MATERIAL	PE
NUMBER OF CONDUCTORS(AWG)	2×2×26AWG+SHIELD
OPERATING TEMPERATURE	-25°C~ + 85°C
PROTECTION CLASS	IEC IP67,IN MATED CONDITION
XXXXXX	XXXXXX

REV	CHG.	DATE	DESCRIPTION	REVISION

MALE END VIEW

P1


- 1.OR/WH(+tx)
- 2.BU/WH(+rx)
- 3.BU(-rx)
- 4.OR(-tx)

MALE END VIEW

P2

- 1.OR/WH(+tx)
- 2.OR(-tx)
- 3.BU/WH(+rx)
- 4.N/C
- 5.N/C
- 6.BU(-rx)
- 7.N/C
- 8.N/C

12345678



SOURCE DRAWING-FOR REFERENCE ONLY

APPROVED BY		DATE	
CHECKED BY	ALEX	DATE	
DRAWING BY	SGY	DATE	2023.8.9
TOLERANCE UNLESS OTHERWISE SPECIFIED	CABLE LENGTH	TOLERANCE	
	ALL LENGTHS	+4%(OR 50mm) OF LENGTH -0%(OR 0mm) OF LENGTH WHICHEVER IS GREATER	
	STRIP LENGTH	TOLERANCE	
	0-7mm	±1.0mm	
	8-29mm	±1.5mm	
	30-49mm	±2.0mm	
	50-99mm	±3.0mm	
70-100mm	±4.0mm		
over 100mm	±5.0mm		

UNITRONICS®

UNITS mm

DESCRIPTION:
CBL-M8AM4-RJ-2

1st Angle Projection

PART NO.

REV	A	SHEET	1 OF 1
-----	---	-------	--------